



SPACE 07 – Decorative Pendant Linear Light



Finish



110°
80°

3000K

CRI
>90

IP20

CE


SMD 2835

5 YEARS
GUARANTEE

Quick Info

- General Lighting, Pendant Direct & Indirect
- SMD 2835 LED: 38W, CRI>90
- CCT: 3000K Available as Standard
- Beam Angle: 80° ↓ , 110° ↑
- Lumen Output: Up to 2450lm System Luminous Flux
- LED Driver: On-Off, Phase Dim, DALI Dim

Light Distribution



Order Info

LED Power	System Power	LED Voltage	LED Current	CRI	CCT	Beam	System Output	Code
38W	40W	36V	1050mA	90	3000K	80° ↓ 110° ↑	2450lm	S07A-9308040F-BR-U S07A-9308040F-BN-U S07A-9308040F-CB-U S07A-9308040P-BR-U S07A-9308040P-BN-U S07A-9308040P-CB-U S07A-9308040D-BR-U S07A-9308040D-BN-U S07A-9308040D-CB-U
Code Remark: F=F(ON-OFF) P=P(Phase Dim) D=D(DALI Dim)								

Coding

S07A	-	**	**	**	*	-	**	-	*
Model		CRI/ CCT	Beam Angle	Power	Control		Finish		Accessory
S07A		930	80	40	F		BR		U
SPACE 07		CRI90/ 3000K	80° ↓	40W	On-Off		Brushed Bronze		Uplight
			80° ↓ 110° ↑		P		BN		
					Phase Dim		Brushed Nickel		
					D		CB		
					DALI Dim		Chrome Black		



Project: Application reference