

# SPACE 16 RING

Direct & Indirect Lightngn One Elegant Form  
Smooth Electroplated Finsh with Custom Colors  
Stepless Height Adjustment via Lifting System  
Professional Look with Dcorative Appeal



SPACE 16 RING – Decorative Pendant Light



110°  
36°

3000K

CRI  
>90

IP20


CE

LUMILEDS  
50,000h@L80B10

5 YEARS  
GUARANTEE

- Quick Info**
- General Lighting, Pendant Direct & Indirect
  - Lumileds LED: 28W, 43W, CRI>90
  - CCT: 3000K Available as Standard
  - Beam Angle: 36° ↓ , 110° ↑
  - Lumen Output: Up to 2700lm System Luminous Flux
  - LED Driver: On-Off, Phase Dim, DALI Dim

Light Distribution



Finish



Order Info

| LED Power | System Power | LED Voltage | LED Current | CRI | CCT   | Beam         | System Output | Code                                                                                                                                                                                               |
|-----------|--------------|-------------|-------------|-----|-------|--------------|---------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 28W       | 30W          | 36V         | 800mA       | 90  | 3000K | 36° ↓ 110° ↑ | 1900lm        | S16A-9303630F-BR-U<br>S16A-9303630F-BN-U<br>S16A-9303630F-CB-U<br>S16A-9303630P-BR-U<br>S16A-9303630P-BN-U<br>S16A-9303630P-CB-U<br>S16A-9303630D-BR-U<br>S16A-9303630D-BN-U<br>S16A-9303630D-CB-U |
| 43W       | 46W          | 36V         | 1200mA      | 90  | 3000K | 36° ↓ 110° ↑ | 2700lm        | S16C-9303646F-BR-U<br>S16C-9303646F-BN-U<br>S16C-9303646F-CB-U<br>S16C-9303646P-BR-U<br>S16C-9303646P-BN-U<br>S16C-9303646P-CB-U<br>S16C-9303646D-BR-U<br>S16C-9303646D-BN-U<br>S16C-9303646D-CB-U |

Code Remark: F=F(ON-OFF) P=P(Phase Dim) D=D(DALI Dim)

Coding

| S16A                          | - | ***                 | **                 | **        | *                                   | -                                              | **           | - | * |
|-------------------------------|---|---------------------|--------------------|-----------|-------------------------------------|------------------------------------------------|--------------|---|---|
| Model                         |   | CRI/ CCT            | Beam Angle         | Power     | Control                             | Finish                                         | Accessory    |   |   |
| S16A<br>SPACE 16 Ring-400-30W |   | 930<br>CRI90/ 3000K | 36<br>36° ↓        | 30<br>30W | F<br>On-Off                         | BR<br>Brushed Bronze                           | U<br>Uplight |   |   |
| S16C<br>SPACE 16 Ring-600-46W |   |                     | 36<br>36° ↓ 110° ↑ | 46<br>46W | P<br>Phase Dim<br><br>D<br>DALI Dim | BN<br>Brushed Nickel<br><br>CB<br>Chrome Black |              |   |   |

Project: Application reference



Simply lift or pull down the luminaire to achieve your desired height.

